



8500 Fowler Ave • Pensacola, FL 32534
(850) 476-9838 • 1-800-988-2233 • FAX (850) 476-8618 • 1-800-990-2233

Build Your Inquiry

Gaskets

1. Thickness

1/16"

1/8"

Other: _____

2. Pressure Rating

150#

300#

600#

Other: _____

3. Style

Ring

Full Face

Spiral Wound*

4. Material

Red Rubber

Non-Asbestos

Neoprene

Viton®

EPDM

PTFE

Other: _____

Is a specific manufacture and series required:

Date: _____

Customer: _____

Job# _____

Attn: _____

Fasteners

1. Type

Bolt

Stud

Other: _____

2. Grade / Alloy

A307 A

GR 5

A307 B

18-8 S/S

316 S/S

B7

B8

B8M

Other: _____

3. Finish

Plain

Zinc

HDG

Cadmium

Xylan

Other: _____

4. Special Length

Is a specific manufacture and series required:

Nuts

1. Type

Finished

Heavy

Other: _____

2. Grade / Alloy

A563 A

GR 5

18-8 S/S

316 S/S

2H

B8

B8M

Other: _____

3. Finish

Plain

Zinc

HDG

Cadmium

Xylan

Other: _____

Kit Qty	Size
	1/2"
	3/4"
	1"
	1-1/4"
	1-1/2"
	2"
	2-1/2"
	3"
	3-1/2"
	4"
	5"
	6"
	8"
	10"
	12"
	14"
	16"
	18"
	20"
	22"
	24"
	26"
	30"
	34"
	36"
	42"
	48"
	54"

Restrictions

Domestic

Import

Import (Non China)

*Spiral Wound gaskets are available in a variety of styles. [Please click here for additional information](#)

**Special packaging is available upon request.

All fasteners conform to ASME B16.5 flanges. If different lengths are needed please note in the "Special Length" section.